


K2-1.0II Series for 1.9mm [75mil] Pitch


K2 1.0 Series Plunger Tip Styles

Unit: mm [inch]


Pin Length: 24.6mm [0.969inch.]




K2-1.0 II A-6.3M-5
Plunger Material: SK (Steel)




K2-1.0 II AH-6.3M-3
Plunger Material: SK (Steel)




K2-1.0 II CR-6.3M1.3-6
Plunger Material: SK (Steel)




K2-1.0 II ER-6.3M1.3-2
Plunger Material: BeCu




K2-1.0 II G-6.3M1.3-6
Plunger Material: BeCu




K2-1.0 II H-6.3M-3
Plunger Material: BeCu




K2-1.0 II HN-6.3M0.9-1
Plunger Material: SK (Steel)



K2-1.0 II K-6.3M1.3-4
Plunger Material: BeCu



K2-1.0 II Q-6.3M-2
Plunger Material: SK (Steel)




K2-1.0 II U-6.3M1.3-7
Plunger Material: BeCu

スプリングピン仕様 Spring Pin Specifications

推奨ストローク Operating Travel	2.87mm [0.113inch]
荷重 Spring Force at Operating Travel	100gf [3.53oz.]
初期荷重 Initial Force	29gf [1.02oz.]
最大ストローク Max Travel	4.3mm [0.169 inch]
スプリング耐久回数 Life Span at Operating Travel	10万回 (100K Cycles)
抵抗値 Resistance (Typ.)	35m
最大許容電流値 Current Rating (Typ.)	4.8A
使用温度 Operating Temp.	45 125

Material/Finish	
Plunger	SK (Steel) or BeCu / Au
Barrel	Nickel Silver / Au
Spring	Music Wire / Au
Ball	Brass / Au



リセプタクル品名 Receptacle

K2 1.0S 4
(末端加工無し / No Termination)



K2 1.0S 4 U
(ソルダーカップ付 / with Solder Cup)



K2 1.0S 6
(末端加工無し / No Termination)



K2 1.0S 6 U
(ソルダーカップ付 / with Solder Cup)



リセプタクル仕様 Receptacle Specifications

Material/Finish	Nickel Silver / Au
-----------------	--------------------

*All specifications are subject to change without notice.